

# Stradus<sup>®</sup> 532-40


The Stradus<sup>®</sup> diode laser module is a fully integrated, plug and play, and self-contained laser module. The patented sealed optical cavity and the innovative electronics give the Stradus<sup>®</sup> laser unparalleled power stability, beam pointing stability, and low noise over time and temperature. Vortran's Graphical User Interface (GUI) software allows the user to control and monitor the module remotely via USB or RS-232.



Specifications	
Wavelength (nm)	532 ± 1
Power Output (mW)	40 (-0%, +10%)
Spatial Mode	TEM <sub>00</sub>
Beam Diameter (mm, 1/e <sup>2</sup> )	~0.8
Beam Divergence (mrad)	~1.0
M <sup>2</sup> (typical)	< 1.25
Beam Circularity	> 90%
Beam Centration (mm)	< 0.5
Beam Alignment (mrad)	< 5
Pointing Stability (µrad/°C)	< 5
Power Stability (over 24 hours)	< 0.5%
Polarization Orientation	Vertical ±2°
Polarization Extinction Ratio	>100:1
RMS Noise (10Hz to 10MHz)	<0.5%
Modulation	Limited (Contact for details)
Input Power (Head)	12V DC, 1.5A (max)
Input Power (Control Box)	90-250 VAC, 50/60Hz
Storage Temperature	-10°C to +60°C
Operating Temperature	+10°C to +45°C
Laser Head Weight	210g
Communication	Mini-USB and RS-232
CDRH Class	Class IIIb
ESD Protection	Class 4
EU Compliance	CE Mark Certified with control box
RoHS Compliance	EU and China

Note: Specifications guaranteed only at full power

- Medical, Biomedical & Industrial
- Patented Sealed Optical Cavity
- Self-contained & Compact
- Excellent Beam Quality
- Low Noise
- USB or RS-232 Interface with GUI
- OEM Head or End-user Systems



## Graphical User Interface Software

