

4304 LaserSource, 4A



- 4A range
- 8V compliance
- 0.1mA resolution
- <30uA noise
- USB and RS-232 interfaces
- Optional QCW mode

The 4304 LaserSource provides up to 4A of current, with excellent noise and accuracy specs. A good choice for applications such as c-mount and TO-3 devices operating up to 4A. Like all 4300s, the 4304 is also available with optional Quasi-CW (QCW) mode.

High Compliance

The 4304 features a high 8V compliance for higher voltage applications, such as LED testing or quantum cascade lasers, as well as excellent performance with lower voltage laser diodes.

Simple User Interface

The 4304's user interface is remarkably simple... so easy to use, you'll have it up and running in no time. Unlike other instruments which rely on 7-segment LED displays and a confusing array of indicators and buttons, the 4304 instead presents the information on a high contrast VFD display in an easy-to-read format. The 4304 displays current, voltage, and photodiode current simultaneously... no need to toggle through the readings like on most instruments. Settings and error messages are in clear English, not cryptic codes and flashing status lights.

Optional Quasi-CW (QCW) Mode

The 4304 offers an optional QCW mode (see the 4304-QCW model), a feature not found in most other laser drivers in its class. Many applications require the low duty cycle, high current pulses that QCW offers to manage thermal loading on the device. With rise times of less than 20 μ s, and pulse widths as narrow as 100 μ s, the 4304-QCW offers an effective and low-cost QCW solution.

Standard Computer Interfaces

The 4304 includes both USB and RS232 computer interfaces, allowing for quick and easy connection to a PC for remote operation. In addition, the LaserSource's command set is compatible with ILX and Newport controllers, allowing you to leverage any existing software you may have already developed.



Ground Loops Eliminated

Like all LaserSources, the 4304 includes isolated inputs and outputs. In technical terms, this means that every input and output signal is electrically isolated, so that offset voltages, ground connections, and AC noise will not "bleed" into other parts of the electronics. Even the photodiode input is fully isolated from the laser output, ensuring full isolation of the laser output. In practical terms, this means it's impossible to create a ground loop through the LaserSource, a common problem in laboratory setups where several different instruments are used in the same test. No other driver on the market has this capability.

Analog Modulation

The 4304's analog interface supports modulation rates up to 50kHz.

Specifications	
CW Mode Specifications	
LASER CURRENT	
Range (mA)	0 – 4000
Resolution (mA)	0.1
Accuracy (\pm [% set+mA])	0.05% + 0.8
Stability (ppm, time)	< 10, 1 hour
Temperature Coeff (ppm/°C)	50
Noise/Ripple (μ A rms)	< 30
Transients (μ A)	< 400
Compliance Voltage (V)	8
Modulation Bandwidth (kHz)	50
Modulation Input Range	0 – 10V, 10k Ω
PHOTODIODE CURRENT	
Range (μ A)	25 – 20000
Resolution (μ A)	1
Accuracy (\pm [% set+ μ A])	0.05% + 2
Stability (ppm, time)	< 200, 24 hours
Temperature Coeff (ppm/°C)	< 200
PD Bias (V)	0 to -5V, software programmable
LASER VOLTAGE	
Range (V)	0 – 8
Resolution (V)	0.001
Setpoint Accuracy (\pm [% set+V])	0.05% + 0.005
Measurement Accuracy (\pm [% reading+V])	0.05% + 0.004
LIMITS	
Current Limit Accuracy (mA)	40
Voltage Limit Accuracy (\pm % FS)	2.5%
GENERAL	
Display Type	2x20 VFD
Laser Connector	DB-9, female
Photodiode/Interlock	On LDD connector
Computer Interface	USB 2.0 Full Speed (Type B), RS-232 (DB-9, male)
Input Power	100V / 120V / 230V, 50 / 60Hz
Size (H x W x D) [inches (mm)]	3.47 (89) x 8.5 (215) x 12 (305)
Operating Temperature	+10°C to +40°C
Storage Temperature	-20°C to +60°C