meadowlark optics

Analog Liquid Crystal Controller

Meadowlark Optics is excited to announce the release of the Model B1010, our new Analog Liquid Crystal Controller. This liquid crystal (LC) driver is designed to integrate with any single (standard) Meadowlark Optics LC device currently offered as well as any nematic Liquid Crystal device compatible with the specifications listed. Independent voltage settings allow easy and repeatable selection of two retardance values. Often, it is desirable to modulate between the two states. For example, switching between quarter-wave and three quarter-wave retardance changes linearly polarized light between left and right circular. A manual toggle allows easy switching between two states. Banana jacks between the knobs allow for continuous voltage monitoring without interfering with LC device connections. Each Meadowlark Optics Liquid Crystal Variable Retarder is supplied with a plot of its actual retardance versus voltage. Using your Model B1010 Controller and this retardance plot ensures accurate retardance to voltage correlation.

SPECIFICATIONS	
Output Voltage	0 to 20 V _{AC} , RMS, maximum
Fundamental Drive Waveform	2 kHz AC square wave
External Modulation (input)	None
Output Bias	± 10 mV _{DC}
Power Requirements	$12\mathrm{V_{DC}}$ 200 mA or 9V battery External power supply included $100\text{-}240\mathrm{V_{AC}}$ 50-60 Hz, 0.3 A International Plugs
Battery Life	1 hour (intended for convenience, not as a primary power source)
External Dimensions (W x D x H)	3.3 x 6.0 x 2.2 in.
Weight	< 1 lb.
	Compliant
CE Compliance	Compilant
	NFORMATION



Key Features

Convenient, stand-alone benchtop operation

Versatile – compatible with all standard Meadowlark Optics liquid crystal devices

> Out-of-the-box functionality Sets up in minutes

Optional battery supply

Banana jacks allow for easy multimeter attachment

Liquid Crystal Suite

Variable Retarders

Liquid Crystal Variable Retarder UV Variable Retarder MWIR Variable Retarder OEM LCVR

Rotators

Achromatic High Speed Rotator **Binary Rotator** Polarization Rotator

Shutters / Attenuators

Achromatic High Speed Shutter High Contrast Shutter Variable Attenuator

Controllers

Analog Controller FLC Controller LC Digital Interface Controller Temperature Controller Two Channel High Voltage Controller