



# Time & Frequency Analyzer



The Moku:Go Time & Frequency Analyzer measures intervals between configurable start and stop events with sub-ns precision. Select between continuous, windowed, or gated acquisition mode, compute histograms of interval duration losslessly and in real time, and log high-resolution event timestamps to on-board storage. Output the measured interval count or current interval to analog output channels for active feedback control.



No. of independent interval analyzers <b>2</b>	Jitter <b>&lt;50 ps</b>	Clock stability <b>25 ppm</b>	Digital resolution <b>7.8 ps</b>	Max interval rate <b>15 MHz</b>	Histogram <b>Real-time and lossless</b>
---	----------------------------	----------------------------------	-------------------------------------	------------------------------------	--

## Features

- Low device jitter of <50 ps for high timing resolution analysis
- Up to two independent event detectors with configurable thresholds on rising edge, falling edge, or both
- Lossless, real-time histograms with a minimum bin width of 7.8 ps
- Output interval count or current interval with adjustable scaling factor
- High-resolution raw event timestamp logging to on-board storage for post processing
- Combine with any other instruments in Multi-instrument Mode for system level characterization or feedback control

## Specifications

- No. of independent interval analyzers: 2
- Jitter: <50 ps
- Digital resolution: 7.8 ps
- Input frequency range: DC to 30 MHz
- Input trigger threshold range:  $\pm 5$  V, or  $\pm 25$  V
- Maximum interval rate: 15 MHz
- Acquisition modes: continuous, windowed, or gated
- Interpolation mode: none or linear
- Event logging rate:
  - up to 31.25 Mevnt/sec burst
  - up to 10 Mevnt/sec continuous
- Output range: 10 Vpp
- Output mode: interval count or current interval

## Applications

- Oscillator analysis
- Photon counting
- Jitter analysis
- Linear optical quantum computing
- Pulsed laser stabilization